



2025 FWD Rules

1. Body

- a. Any front-wheel-drive compact car with a four-cylinder engine is permitted. All cars must remain O.E.M.-appearing body. Convertibles, Honda CRX and/or two-seat sports cars are not allowed.
- b. The maximum wheelbase must be one hundred seven (107) inches with a maximum difference of one (1) inch from side to side. O.E.M. steel unaltered floor pans only. Inner fenders may not be removed. The hood and trunk lid/hatch must be securely fastened. All doors must be securely welded or bolted.
- c. All glass, exterior lights, chrome, plastic trim, and hood insulation must be removed. Hood may be gutted. Dash may be removed or remain in place. Maximum seven (7) inch front and rear sun visors are permitted. Opera window may be closed. Skirting is permitted but must maintain O.E.M. in appearance.
- d. Main Firewall must remain in the vehicle.
- e. The Vehicle Identification Number (V.I.N.) must remain clearly visible and unaltered in at least one of the O.E.M. locations. Any car missing the V.I.N. will not be allowed to compete.
- f. Bumpers must be OEM or can be use aftermarket, Must not be wider than factory. Front and rear tow hooks are mandatory.
- g. Aftermarket nose piece can be used. Must not be wider than front tires.
- h. One horizontal bar at a maximum one and three-quarters (1.75) inches O.D. tying front frame horns together ahead of radiator is permitted. Must stay inside frame rails. One additional bar of a maximum one (1) inch O.D. may be added for radiator protection but must be behind the bumper and within the limits of the body and no wider than O.E.M. frame horns. Reinforced bumpers are not allowed.
- i. If rear speaker dash is removed, must add minimum 1.5 round tubing to connect strut towers.

2. Braking System

- a. Must utilize steel, unaltered, O.E.M. operative, four-wheel disc or drum brakes, and must match year, make and model of car used.
- b. Master cylinder must be O.E.M. and in O.E.M. location. c. Brake shut-off and/or bias adjuster is not allowed. Electronic brake actuators are not allowed.
- c. Steel brake lines are mandatory and must be visible for inspection.
- d. Anti-lock braking systems are not allowed. Parking brakes are permitted but must be disabled while racing.
- e. Brake shut offs and/or bias adjusters are not allowed.
- f. Must maintain minimum O.E.M. dimension for hubs, rotors, and calipers.

3. Cockpit

- a. Minimum three windshield bars mounted in front of driver. Aluminum high-back racing seats are required and must be securely mounted to roll cage using three hundred seventy five one thousandths (0.375) inch bolts with washers. Driver must be sealed off from track, engine, transmission, and fuel cell/tank. Mirrors are not allowed. Trimming/Gutting allowed as long as integrity and aesthetics of the car are

not taken away from stock appearing. All flammable material must be removed. Front and rear firewalls must remain and have no holes. The interior must remain open.

- b. Loose objects and/or weights are not allowed.
- c. Air bags are not allowed.
- d. Rear view mirrors are not allowed.
- e. Radios must be removed.

4. Drive Shaft

- a. All drive shafts must be O.E.M.

5. Electrical System

- a. One (1) 12-volt battery is permitted only. Must be securely mounted with positive terminal covered. Battery must be in Marine type case if mounted in driver compartment and battery (not battery box) must be secured with metal brackets to floor or roll cage and then covered.
- b. Only O.E.M. starter is permitted and must be in O.E.M. location. Car must leave initial staging area on demand and unaided or go to rear of that race.
- c. Unapproved cameras, transmitting, and/or listening devices are not allowed. (Exception: one-way RACEceiver radio used by Officials).
- d. Must utilize one 12-volt ignition system only. All ignition components must be unaltered, O.E.M. and match manufacturer.
- e. Factory harness may be trimmed to a single fuse setup, Stand alone OEM Injection/harnesses allowed. Aftermarket analog tach, oil pressure and water temp gauges only. Vehicle computers (ECU) should be stock appearing and mounted in accessible location for inspection. Aftermarket programming of the ECM is permitted.
- f. All ignition parts must remain out of reach of the driver.
- g. Kill switch is required and must be within easy reach of the driver. The switch must be clearly marked "OFF" and "ON."
- h. Transponders must be mounted vertically on the right-side fire-wall.
- i. No Bluetooth or cellular devices are allowed in race car.

6. Engine

- a. Stock production 4cyl engines no larger than 2.5L
- b. Solid engine mounts and/or safety chains are permitted.
- c. Engine must match body GM to GM, ford to ford honda to honda etc
- d. Only 3-or 4-cylinder in-line engines are permitted.
- e. All engine components must be unaltered O.E.M. Drive belts may be removed. Balance shafts may be removed.
- f. Must use O.E.M. crank, rods, valve sizes, stroke, etc. Aftermarket racing heads are not allowed. Overbore and decking allowed for rebuild. Must use stock replacement pistons.
- g. Turbo-charged, super-charged, rotary engines are not allowed.

- h. Unapproved alterations to any engine are not allowed.
- i. Maximum two (2) inch diameter (O.D.) exhaust pipes from manifold and must extend past firewall.
- j. factory headers allowed and direct manifold replacement headers allowed. No long tube race headers allowed.

7. Frame

- a. Sub frames must be stock. May be tubed from fire wall back. The required tube size is 2x2 inch square.
- b. Wheelbase must be a maximum of one hundred seven (107) inches with a difference from side to side of one (1) inch.

8. Fuel System

- a. Must have complete, unaltered, O.E.M. fuel system for make and model of car.
- b. Gasoline only, maximum 93 octane. E85 and/or performance additives are not allowed.
- c. A gas tank ahead of the rear axle is permitted but must have a shield installed beneath. Gas tank behind rear axle must be replaced with a maximum eight (8)
- d. relocated to trunk area; Must mount with minimum one (1) inch square tubing or two (2) solid steel straps around entire cell, two (2) inches wide and one eighth (0.125) inch thick.
- e. Metal firewall or cell cover must be between driver and cell. Fuel cell vent, including cap vent, must have check valve. If racing fuel cell does not have aircraft- style positive seal filler neck/cap system, a flapper, spring, or ball-type filler rollover valve is required.
- f. External electric fuel pump wired to the ignition switch is permitted with aftermarket fuel cells.
- g. Cool cans are not allowed. Fuel lines through the driver compartment must be made of steel. Aftermarket fresh air pipe and air filter is permitted (Ram Air or direct outside air flow is not allowed).

9. Rear-End

- a. Must be O.E.M. Must match year, make, and model.

10. Roll Cage

- a. A six-point, full-perimeter roll cage is required. Must use minimum one and one-half (1.5) inches O.D. with ninety-five one thousandths (0.095) inch wall thickness tubing. Rear hoop must have "X" bracing configuration. Rear kickers are required. Forward brace bar is permitted from main cage to front strut tower. Must have one and one-quarter (1.25) inches minimum O.D. cross bar in top halo. Cage must be electric welded and attached using adequate plating at a recommended minimum of one-quarter (0.25) inch. Iron, galvanized pipe or fittings, square tubing, brazing, or soldering is not allowed.
- b. A minimum of three (3) horizontal door bars on the driver's side and two (2) horizontal door bars on passenger side are required. Both sides must have vertical bracing from top to bottom door bars. All tubing must be minimum one and one-half

(1.5) inches O.D. with ninety-five one thousandths (0.095) inch wall thickness. Steel door plates of 18 gauge or forty-nine one thousandths (0.049) inch minimum thickness must be securely welded to the outside of door bars on driver side. Plate must cover the area from top door bar to frame and from rear down post to five (5) inches in front of seat. Must be visible for inspection.

- c. Roll bars within the driver's reach must be padded with a material deemed acceptable by Official(s). Fire retardant material is highly recommended.
- d. Installation and workmanship must be acceptable to Official(s).
- e. With helmet on and driver securely strapped into the racing seat, the top of driver's head must not protrude above the roll cage.
- f. A tow hook on the front and rear is mandatory.

11. Springs, Shocks, & Struts

- a. All shocks and struts must remain O.E.M. in O.E.M. location and match year, make, and model.
- b. Only O.E.M. springs or O.E.M. replacement springs are permitted. Racing springs are not allowed. Springs may be modified but must mount like factory springs. Spring rubbers are permitted. Bump stops (including O.E.M.) are not allowed. Shock bellows are not allowed.
- c. No altering of Strut and O.E.M. shock.
- d. Springs must must be in the O.E.M location.
- e. No adjustable shocks or struts.
- f. No pin down shocks or struts.

12. Steering

- a. Steering must be unaltered O.E. and remain within the original bolt pattern for the type of car used. Steering linkage must be unaltered approved O.E.M. in stock location, replaceable by stock part and must match frame.
- b. May be modified to suit the driver but must remain on the left side of cockpit (no center steering).
- c. Factory steering column may be replaced with factory length, from the factory collapsible shaft, with solid steering shaft. Quick-release metal coupling on steering wheel is permitted. Plastic couplings are not allowed.
- d. Aftermarket remote reservoir power steering is not allowed.

13. Suspension

- a. All components and mounts must be unaltered, O.E.M. and match year, make and model of car used. (Exception: Highly Recommended right rear safety hub, 1987-95 Caravan hub assembly for example).
- b. Brace bars are permitted between strut towers in front and rear.
- c. Front struts braces be made from the front, back, and side of strut towers to frame. All braces must be welded separately.
- d. Rear struts braces be made from the front, back, and side of strut towers to frame. All braces must be welded separately.
- e. Weight jacks, modifications, racing components, aftermarket and/or homemade traction devices are not allowed.

- f. No more than two (2) degrees of camber is permitted on any wheel (Exception: The right front wheel may have a maximum of four (4) degrees of camber).

14. Tires and Wheels

- a. Only O.E.M. unaltered 13-, 14-, 15- or 16-inch-diameter D.O.T. passenger tires are permitted. Minimum 45 Series, M, N, P, Q, R, S, T and H speed rated tires only are permitted. Racing, mud, snow and/or recap/retread tires are not allowed. Softening, conditioning, grinding, sanding, siping and/or grooving is not allowed.
- b. Must utilize aftermarket steel wheels with standard bead bump and maximum seven (7) inch width and four (4), five (5) or five and one-half (5.5) inch offset. Reinforcing of wheels is recommended.
- c. Factory aluminum wheels allowed
- d. Tires and wheels do not have to be the same series, size and offset.
- e. Wheel spacers and/or bleeder valves are not allowed.
- f. Must use one (1) inch O.D. steel lug nuts on steel wheels.
- g. Mixing of steel/aluminum wheels allowed.

15. Transmission

- a. Must utilize O.E.M. transmission.
- b. All forward and reverse gears must be operational. The flywheel, flex plate, clutch assembly and torque converter must be unaltered O.E.M. for the make car used.
- c. Mini-clutches and/or couplers are not allowed. Must have inspection hole in bell housing (accessible from top).
- d. Transmission coolers in driver compartment are not allowed.
- e. CVT transmissions are not allowed.
- f. Locked differentials or lsd allowed

16. Weight

- a. Ballast (extra weight) All cars allowed 50#. Must be properly secured, painted and have car #
- b. All Non VVT/Vtec cars are required to weigh a minimum of two-thousand three hundred (2,300) pounds.
- c. All cars utilizing VVT/Vtec must weigh 2450 pounds. If under weight, weight must be added behind the rear strut towers. Weight must be properly affixed, painted and have car # Any car not meeting this weight will Disqualified.